

Technical Data Sheet

SIZE : VF650/55R26.5 V-FLEXA 171D

Tire Size	VF650/55 R 26.5
Conversion Size	---
Pattern	V-FLEXA
Version	STEEL BELTED
PR	---
Star Rating	---
LI/SS	171 D
TT/TL	TL
ECE Approval No	---
Tire Segment	AGRICULTURE
TRA Code	---
Rec Rim Width	AG20.00
Alt. Rim Width	---
SW (mm) ± 2%	644
O.D (mm) ± 2%	1389
SLR (mm) ± 2%	591
RC (mm) ± 2%	4100
NSD (mm) ± 1	24.5
No. of Lugs	---
TKPH	---
Wt. (kgs) ± 3%	177.710
Tube	---
Tube Valve	---
Flap	---



Application	IMPLEMENT
-------------	-----------

Infl. Pressure (bar)	0.8	1.2	1.6	2.0	2.4	2.8
Speed (kmph)	Load capacity (kg/tyre)					
70	2405	3075	3745	4250	4920	5595
65	2640	3380	4120	4670	5410	6150
50	3090	3955	4820	5465	6330	7195
40	3405	4360	5310	6025	6975	7930
10	4335	5545	6755	7660	8870	10085

Note: All Dimensions conform to ETRTO Standards

Prepared by :-
Amit More



Approved by :-
Mr. Shekhar Yadav

