

TECHNICAL SPECIFICATION

Pattern Name RIDEMAX FL 693 M

Version STANDARD
 Type TL
 Tire Size 650/55 R 26.5
 LI/SS 169 D



Dimensions (U/M International standard):

Section Width (mm) 645
 Overall Diameter (mm) 1389
 Static Loaded Radius (mm) 608
 Rolling Circumference (mm) 4216
 SRI 650
 Rim Rec AG 20.00

Applications Trailer / Tanker / Spreader

Description RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

LOAD CAPACITY TABLE (kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1965	2230	2705	3130	3605	4085	4400	4880	5300
65	2150	2440	2960	3425	3945	4470	4815	5340	5800
50	2600	2950	3585	4145	4775	5410	5830	6460	7020
40	2920	3315	4025	4660	5370	6080	6550	7260	7890
25	3395	3850	4675	5410	6235	7060	7610	8435	9165
10	3865	4385	5325	6160	7100	8040	8670	9605	10440